

# SPRING CLAMP TERMINAL BLOCKS

## PANEL MOUNT TERMINAL BLOCKS

These blocks are an excellent solution for extremely compact wiring applications. The Terminal Blocks are "modular" and can be stacked to form multi pole assemblies.

The stacked assemblies are mounted on the panel surface using mounting End Plates at both the ends. Comb type shorting links can be used for cross connection.

In CSCP2.5T2 Terminal Blocks, there are two connection points each on both sides.

The terminals marked with can be used in potentially explosive atmosphere. For detailed information refer page E-44.



	CSCP2.5T	CSCP2.5T2		
Terminal Block Pitch	5 mm	10 mm		
Height x Width	27 x 35 mm	27 x 35 mm		
Connection Possibility	0.5 to 2.5 sq.mm 0.5 to 4 sq.mm	0.5 to 2.5 sq.mm 0.5 to 4 sq.mm		
Stripping Length	14 mm	14 mm		
Insulation Material / Comparative Tracking Index	Polyamide 66 / I	Polyamide 66 / I		
Type of Connection	2 Spring clamp connections	4 Spring clamp connections		
Approvals				
Rated Connecting Capacity	22-14 AWG * 0.5-2.5 sq.mm 22-12 AWG	22-14 AWG * 0.5-2.5 sq.mm 22-12 AWG		
Voltage Rating Rated Impulse Voltage/Pollution Degree	600 V 800 V / 3 600 V	600 V 800 V / 3 600 V		
Current Rating	20 A 24 A 25 A	20 A 24 A 25 A		
Other Approvals				
	<b>Type Cat. No.</b>	<b>Std. Packing in Pcs.</b>	<b>Type Cat. No.</b>	<b>Std. Packing in Pcs.</b>
Terminal Block	CSCP2.5T	100	CSCP2.5T2	100
End Plate	EPCSCP2.5T	25	EPCSCP2.5T	25
Insulated Comb Type Shorting Link (2 way)	CA803/1	100	CA803/1	100
Screw Driver for actuating the Spring Clamp	SCS0.5/3	10	SCS0.5/3	10
Actuator for actuating the Spring Clamp	SCA2.5	1	SCA2.5	1
Marking Tags (K Type)	MT4	100	MT3	100

\* For Stranded conductor only

